

# ULPN-266

## Deep UV Nanosecond Pulsed Fiber Laser

Industry Leading Reliability for  
Micromachining Applications  
**DEEP UV**



**NEW**

### FEATURES

- ▶ 10 Watts Output Power at 266 nm
- ▶ 2  $\mu$ J pulses at 1.3 ns
- ▶ Maintenance Free Operation
- ▶ Robust Compact Package
- ▶ Lightweight Optical Head

### MICROMACHINING APPLICATIONS

- ▶ Cutting & Drilling
- ▶ Texturing & Marking for PCBs, Flex Circuits
- ▶ Glass, Diamond & Teflon
- ▶ Selective Material Removal for LEDs & Displays

**ULPN-266** establishes a new deep ultraviolet standard for 266 nm reliable power.

**ULPN-266** laser is designed for micro-cutting, drilling, texturing, marking and selective material removal on challenging materials such as glass, diamond and Teflon. Exceptional IPG non-linear crystal robustness enables **industry-leading laser reliability and stability of process parameters**. The pulse energy is nearly independent of pulse repetition rate, resulting in **the highest productivity at the maximum average power**.

The fiber-based architecture allows for an **easy-to-integrate, compact, lightweight optical head** tethered to a remote air-cooled module. The small, flexible form factor is **ideal for material processing workstations** utilized in the display, electronics, medical device and other industries.

# ULPN-266

## Deep UV Nanosecond Pulsed Fiber Laser

### Optical Characteristics

Wavelength, nm	266
Mode of Operation	Pulsed
Output Power, W	Up to 10
Power Tunability, %	10-100
Pulse Energy, $\mu$ J	Up to 2
Pulse Duration, ns	1.3
Repetition Rate, kHz	100-2700
Beam Mode Quality, $M^2$	<1.2

### General Characteristics

OEM Laser Module Dimensions (W x D x H), mm	270 x 256 x 89
Optical Head Dimensions (W x D x H), mm	142 x 345 x 80
Optical Head Weight, kg	5
Cooling	Optical Head – Passive Conductive Laser Module – Forced Air
Supply Voltage, VDC	24
Power Consumption, W	<200

### Learn More



Contact Us:

[DeepUV@IPG Photonics.com](mailto:DeepUV@IPG Photonics.com)

MAX. AVERAGE OUTPUT POWER: 20 W  
MAX. PEAK POWER: 5 kW  
PULSE DURATION: 1-10 ns  
PULSE REPETITION RATE: 100-2700 kHz  
WAVELENGTH RANGE: 250-270 nm

DANGER - INVISIBLE LASER  
RADIATION AVOID EYE OR SKIN  
EXPOSURE TO DIRECT OR  
SCATTERED RADIATION  
CLASS 4 LASER PRODUCT

IEC 60825-1:2014

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2023 IPG Photonics Corporation. All rights reserved.