

WELDING LASERCELL

AUTOMATED LASER WELDING SYSTEM



FEATURES

- ▶ Automated laser welding system with proven weld process developed by IPG
- ▶ IPG laser source and beam delivery optimized for the application
- ▶ Manual and automated part loading and positioning options
- ▶ Single and dual robot configurations
- ▶ Part positioning and multi station load unload options to meet specific manufacturing needs



BENEFITS

- ▶ Typically 5X-10X faster than alternative technologies for lower production costs
- ▶ IPG process knowledge accelerates implementation and reduces schedule risk
- ▶ Optional real-time weld measurement ensures good welds, preventing part failures and recalls
- ▶ Optional tooling development services from IPG increases part yield and accelerates time to first part
- ▶ Single-vendor solution from experts in both laser processing and tooling development


The **Welding LaserCell** is configurable with virtually all IPG lasers and beam delivery heads. IPG will provide guidance on the best equipment selection for specific applications and material-thickness combinations based on proven welding implementations.

WELDING LASERCELL

AUTOMATED LASER WELDING SYSTEM


Part Loading and Positioning Options

CONVEYOR LOADING



Working Volume:
500 mm × 400 mm × 250 mm (LxWxH)
Max Part Weight: 500 kg/pallet


TURNTABLE



Working Volume:
1000 mm × 400 mm × 500 mm (LxWxH)
Max Part Weight: 350 kg/side

TWO AXIS POSITIONER


for Large-Heavy Parts
& Complex Shapes



Working Volume:
1000 mm × 600 mm (LxW)
Max Part Weight: 500 kg

HEAD & TAIL STOCK

for Shafts & Long Cylinders



Working Volume:
1000 mm × 600 mm (LxW)
Max Part Weight: 500 kg

System Specifications

Laser Source	2 - 6 kW IPG industrial CW fiber lasers
Beam Delivery	IPG D30 or High Power Scanning Welding Heads
Dimensions (L × W × H) , mm	4200 × 2200 × 3000
System Control	Industrial PLC controller with HMI using IPG Core
Safety	Class 1
Robot Configuration	Industrial 6-Axis robot with Motion Package and Safety Position Check
Reach/Repeatability, mm	~1800 +/- 0.025

System Options

Laser Source (Options)	Single and Multi-mode 2/4 kW Adjustable Mode Beam lasers with independent core & ring power control	1-2 kW Single-mode and 4-6 kW Multi-mode Rack Mounted or Cabinet Lasers
Real-Time Weld Measurement	Integrated real-time inline coherent imaging (ICI) weld monitoring system measuring weld penetration depth, transverse profile	
Vision	Integrated vision imaging and correction system providing typical weld-to-part accuracy of +50 µm	
Part Loading Options	Manual part loading via system front doors, optional conveyor pass-through or servo turntable with automated entry/exit doors	
Fume Extraction	Integrated fume extraction contained within the laser cell	
Power Meter	Integrated power meter for automatic, programmable measurement of laser power	

Contact Us:



Learn More:

IPGPhotonics.com/contact

lasersystems.ipgphotonics.com/products

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind IPG only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with use of a product or its application. IPG, IPG Photonics, The Power to Transform and IPG Photonics' logo are trademarks of IPG Photonics Corporation. © 2022 IPG Photonics Corporation. All rights reserved.